WEST

| Help | Logout | Interrupt |

| Main Menu | Search Form | Posting Counts | Show S Numbers | Edit S Numbers | Preferences |

Search Results -

Terms	Documents
l1 and (monitor$3 same network$1)	445

Database:

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Refine Search:

```
l1 and (monitor$3 same network$1)
```

| Clear |

Search History

Today's Date: 7/2/2001

DB Name	Query	Hit Count	Set Name
USPT	l1 and (monitor$3 same network$1)	445	L2
USPT	(machine$1 or printer$1) same status$1 same display$3	3026	L1

WEST

| Help | Logout | Interrupt |

| Main Menu | Search Form | Posting Counts | Show S Numbers | Edit S Numbers | Preferences |

Search Results -

Terms	Documents
l1 same (monitor$3 same network$1)	0

Database:

```
US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins
```

Refine Search:

```
l1 same (monitor$3 same network$1)
```

| Clear |

Search History

Today's Date: 7/2/2001

| DB Name	Query	Hit Count	Set Name
JPAB	l1 same (monitor$3 same network$1)	0	L5
PGPB	l1 same (monitor$3 same network$1)	0	L4
USPT	l1.ab. and (monitor$3 same network$1)	18	L3
USPT	l1 and (monitor$3 same network$1)	445	L2
USPT	(machine$1 or printer$1) same status$1 same display$3	3026	L1

WEST

| Help | Logout | Interrupt |

| Main Menu | Search Form | Posting Counts | Show S Numbers | Edit S Numbers | Preferences |

Search Results -

Terms	Documents
l1 same (monitor$3 same network$1)	0

Database:

- US Patents Full-Text Database
- US Pre-Grant Publication Full-Text Database
- JPO Abstracts Database
- EPO Abstracts Database
- Derwent World Patents Index
- IBM Technical Disclosure Bulletins

Refine Search: l1 same (monitor$3 same network$1)   Clear

Search History

Today's Date: 7/2/2001

DB Name	Query	Hit Count	Set Name
EPAB	l1 same (monitor$3 same network$1)	0	L6
JPAB	l1 same (monitor$3 same network$1)	0	L5
PGPB	l1 same (monitor$3 same network$1)	0	L4
USPT	l1.ab. and (monitor$3 same network$1)	18	L3
USPT	l1 and (monitor$3 same network$1)	445	L2
USPT	(machine$1 or printer$1) same status$1 same display$3	3026	L1

WEST

| Help | Logout | Interrupt |

| Main Menu | Search Form | Posting Counts | Show S Numbers | Edit S Numbers | Preferences |

Search Results -

Terms	Documents
l1 same (monitor$3 same network$1)	0

Database:

- US Patents Full-Text Database
- US Pre-Grant Publication Full-Text Database
- JPO Abstracts Database
- EPO Abstracts Database
- Derwent World Patents Index
- IBM Technical Disclosure Bulletins

Refine Search:

```
l1 same (monitor$3 same network$1)
```

| Clear |

Search History

Today's Date: 7/2/2001

DB Name	Query	Hit Count	Set Name
DWPI	l1 same (monitor$3 same network$1)	0	L7
EPAB	l1 same (monitor$3 same network$1)	0	L6
JPAB	l1 same (monitor$3 same network$1)	0	L5
PGPB	l1 same (monitor$3 same network$1)	0	L4
USPT	l1.ab. and (monitor$3 same network$1)	18	L3
USPT	l1 and (monitor$3 same network$1)	445	L2
USPT	(machine$1 or printer$1) same status$1 same display$3	3026	L1

WEST

| Help | Logout | Interrupt |

| Main Menu | Search Form | Posting Counts | Show S Numbers | Edit S Numbers | Preferences |

Search Results -

Terms	Documents
l1 same (monitor$3 same network$1)	0

Database:

- US Patents Full-Text Database
- US Pre-Grant Publication Full-Text Database
- JPO Abstracts Database
- EPO Abstracts Database
- Derwent World Patents Index
- IBM Technical Disclosure Bulletins

Refine Search: `l1 same (monitor$3 same network$1)`   Clear

Search History

Today's Date: 7/2/2001

DB Name	Query	Hit Count	Set Name
TDBD	l1 same (monitor$3 same network$1)	0	L8
DWPI	l1 same (monitor$3 same network$1)	0	L7
EPAB	l1 same (monitor$3 same network$1)	0	L6
JPAB	l1 same (monitor$3 same network$1)	0	L5
PGPB	l1 same (monitor$3 same network$1)	0	L4
USPT	l1.ab. and (monitor$3 same network$1)	18	L3
USPT	l1 and (monitor$3 same network$1)	445	L2
USPT	(machine$1 or printer$1) same status$1 same display$3	3026	L1

WEST

☐   Generate Collection

L3: Entry 1 of 18   File: USPT   Nov 7, 2000
US-PAT-NO: 6145098
DOCUMENT-IDENTIFIER: US 6145098 A

TITLE: System for displaying system status

DATE-ISSUED: November 7, 2000

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Nouri; Ahmad	San Jose	CA	N/A	N/A
Johnson; Karl S.	Palo Alto	CA	N/A	N/A

US-CL-CURRENT: 714/31; 714/47

ABSTRACT:

A fault tolerant computer system for obtaining and displaying, or updating the
status of server components through a remote interface and either a local or
remote client machine without intervention of the server operating system
software. The remote machine accesses the server by use of a dial-in modem
connection, while the local machine accesses the server by a local serial
connection. The components that can be monitored include, but are not limited to,
the following: Power Supplies, Temperatures, Fans, Processors, I/O Groups, I/O
Canisters, Serial Numbers, and Revisions.

35 Claims, 26 Drawing figures Exemplary Claim Number: 25
Number of Drawing Sheets: 26

WEST

☐ | Generate Collection

L3: Entry 2 of 18   File: USPT   Jul 11, 2000
US-PAT-NO: 6088816
DOCUMENT-IDENTIFIER: US 6088816 A

TITLE: Method of displaying system status

DATE-ISSUED: July 11, 2000

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Nouri; Ahmad	San Jose	CA	N/A	N/A
Johnson; Karl S.	Palo Alto	CA	N/A	N/A

US-CL-CURRENT: 714/31; 709/217, 709/224

ABSTRACT:

A fault tolerant method of obtaining and displaying, or updating the status of
server components through a Remote Interface Board and either a local or remote
client machine without intervention of the server operating system software. The
remote machine accesses the server by use of a dial-in modem connection, while the
local machine accesses the server by a local serial connection. The components
that can be monitored include, but are not limited to, the following: Power
Supplies, Temperatures, Fans, Processors, I/O Groups, I/O Canisters, Serial
Numbers, and Revisions.

32 Claims, 26 Drawing figures Exemplary Claim Number: 1
Number of Drawing Sheets: 26

WEST

☐ | Generate Collection |

L3: Entry 7 of 18   File: USPT   Mar 10, 1998
US-PAT-NO: 5727135
DOCUMENT-IDENTIFIER: US 5727135 A

TITLE: Multiple printer status information indication

DATE-ISSUED: March 10, 1998

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Webb; James Francis	Lexington	KY	N/A	N/A
Wedinger; Jeffrey Keith	Lexington	KY	N/A	N/A
Wellman; John Neil	Lexington	KY	N/A	N/A

US-CL-CURRENT: 358/1.14; 358/1.15

ABSTRACT:

Bidirectional communications between a host computer and a selected printer
connected to the host, either locally or by way of a network, are used to provide
a user of the host with access to a substantially real-time, visual and functional
replica of the operator panel of the selected printer. A user at the host computer
may also visually monitor the status of multiple printers at the same time from
the same host display.

15 Claims, 10 Drawing figures Exemplary Claim Number: 1
Number of Drawing Sheets: 7

WEST

☐ | Generate Collection |

L3: Entry 11 of 18   File: USPT   Jun 7, 1994
US-PAT-NO: 5319783
DOCUMENT-IDENTIFIER: US 5319783 A

TITLE: Programmable controller with an operator messaging function

DATE-ISSUED: June 7, 1994

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Zink; Steven M.	Hudson	OH	N/A	N/A
Pietrzyk; Arthur P.	Thomson	OH	N/A	N/A
Schultz; Michael E.	Euclid	OH	N/A	N/A
Tletski; Paul J.	Parma	OH	N/A	N/A

US-CL-CURRENT: 700/18

ABSTRACT:

A programmable controller senses the status of input devices and controls the
state of operating devices in accordance with a stored ladder logic control
program. A memory of the programmable controller contains message data and data
defining a set of expected transitions of the status of selected input devices. An
instruction of the ladder logic initiates execution of a machine language message
program which causes the programmable control to inspect the states of the
selected input devices to determine whether an expected transition has taken
place. When one of the expected transitions occurs, the message data and an
identification of the selected input device are sent to a personal computer
connected to the programmable controller. The personal computer uses the the data
from the programmable controller to formulate an alphanumeric message which is
presented to the operator on a display device.

15 Claims, 12 Drawing figures Exemplary Claim Number: 1
Number of Drawing Sheets: 9